Accessories for the distribution network

Taps, 1-way

EAC 01	272049
EAC 02	272053
EAC 03	272054
EAC 04	272055

EAC 01

- Impedance: 75 Ω
- Frequency range: 5-1,000 MHz (i.e. return path and UHF suitable)
- Solid housing of tin plated zinc diecast
- Insulating capacitors on inputs and outputs
- Conform to: EN 60728-11 and EN 50083-2
- Connections: F connectors
- For indoor mounting

Type			EAC 01	EAC 02	EAC 03	EAC 04
Order no.			272049	272053	272054	272055
Tap loss		dB	8.5	12	16	20
Through loss	5-40 MHz 40-470 MHz 470-862 MHz 862-1,000 MHz	dB	1.5 1.5 1.6 2.0	0.8 0.8 0.8 1.1	0.5 0.5 0.5 0.7	0.5 0.5 0.5 0.7
Directional loss	5-40 MHz 40-1,000 MHz [1]	dB	≥ 30 ≥ 30	≥ 32 ≥ 32	≥ 36 ≥ 36	≥ 38 ≥ 40
Return loss	5-40 MHz 40-1,000 MHz [1]	dB	≥ 20 ≥ 20			
Screening factor	5-300 MHz 300-470 MHz 470-1,000 MHz	dB	> 85 > 80 > 75			
Dimensions		mm	52 x 25 x 50			
Packing unit/weight		pc./kg	1 (10, 200)/0.08			

[1] At 40 MHz, -1.5 dB/octave